



## Compact Rules

1. Any Sub Frame Compact **Car** or **Wagon** 4 or 6 cylinder with a wheel base no more than 108 inches. NO AWD, NO Full Frame or NO Diesel motors allowed.
2. Helmet, Neck brace, long sleeves, pants and closed toe shoes are required to race.
3. **Engine** must be stock to make of car only aftermarket parts that can be used is a set of headers. NO engine cradles or anything added to protect motor or reinforce any areas on the car.
4. **Radiator** should be OEM and stay in stock location.
5. **Battery** two twelve-volt batteries max mounted in a covered box secured to the floor board.
6. **Fuel** stock tank needs to be removed! Boat tank or aftermarket tank can be used and mounted inside of vehicle. Five-gallon tank max. Can use aftermarket electric fuel pump long as on/off switch is labeled inside in arms reach of driver.
7. **Body** remove all glass, mirrors, door handles, headlights, tail lights, bumper covers and interior pieces. Weld, chain or nine wire all doors on vehicle solid. Windshield area should have a chain, wire or bar from roof to cowl to prevent hood from coming in on driver. That piece should be for safety only and not add any strength to vehicle. Hoods and trunk may have 2 pieces of  $\frac{3}{4}$  max size threaded rod in each can also use number nine wire on both maximum six locations on hood and trunk can be wired. One 12-inch hole has to be cut in center of hood. No welding solid of hood or trunk. Trunk may be left in stock location and tucked into a 90. **No added metal to anywhere to reinforce any areas on vehicle. Body creasing and pre-bending allowed, within reason.**
8. **Suspension** Stock steering and suspension no aftermarket spindles or homemade strut towers front end should have some bounce.

9. **Bumpers** must appear stock and not exceed width of the front end but can be reinforced. Thickness of bumper may not exceed 8 inches from front to back. **Example:** cutting ends off and sliding a pipe in will be allowed. May use plate or angle iron to secure bumper from falling off. The piece used may only exceed the width of front bumper pad by a few inches.
10. **Tires** NO Tractor or Digger tires on drive axle. Only Mud/ Snow tires can be used on drive axle. Tubes and valve stem protectors are allowed.
11. **Cage** four post and roll bar are mandatory. No kickers allowed. Stock seat belt must be in good working order or harness may be put in car.
12. **Track Rules** no driver's door shots if official feels hit was intentional car will be blacked flagged from race.
13. When red lights come on all cars are to stop action immediately. If vehicle leaves track area you may re-enter under idle not at full throttle.
14. Any two-digit number can be used must be in bright color so scorers can see it. No profanity or vulgar sayings on vehicle this is a family show.

Updated 6/11/18

**1<sup>st</sup>. \$500**

**2<sup>nd</sup> \$300**

**3<sup>rd</sup> \$100**

**May 26<sup>th</sup>, June 23<sup>rd</sup>, July 21<sup>st</sup>, August 25<sup>th</sup>, September 22<sup>nd</sup>**