



## Compact Rules- Saturday October 21st, 2023

1. Any Sub Frame Compact **Car** or **Wagon** 4 or 6 cylinder with a wheelbase no more than 108 inches. NO AWD, NO Full Frame or NO Diesel motors allowed.
2. Helmet, Neck brace, long sleeves, pants and closed toe shoes are required to race.
3. **Engine** must be stock to make of the vehicle. Only aftermarket parts that can be used as a set of headers. NO engine cradles or anything added to protect the motor or reinforce any areas on the car.
4. **Radiator** should be OEM and stay in stock location.
5. **Battery** two twelve-volt batteries max mounted in a covered box secured to the floor board.
6. **Fuel** stock tank needs to be removed! Boat tank or aftermarket tank can be used and mounted inside the vehicle. Five-gallon tank max. Can use an aftermarket electric fuel pump as long as the on/off switch is labeled inside of arms reach of the driver.
7. **Body** remove all glass, mirrors, door handles, headlights, tail lights, bumper covers and interior pieces. Weld, chain or nine wire all doors on vehicle solid. Windshield area should have a chain, wire or bar from roof to cowl to prevent hood from coming in on driver. That piece should be for safety only and not add any strength to the vehicle. Hoods and trunks may have 2 pieces of  $\frac{3}{4}$  max size threaded rod in each can also use number nine wire on both maximum six locations on hood and trunk can be wired. One 12-inch hole has to be cut in the center of the hood. No welding solid of hood or trunk. Trunks may be left in stock location and tucked into a 90. **No added metal to anywhere to reinforce any areas on the vehicle. Body creasing and pre-bending allowed, within reason.**
8. **Suspension** Stock steering and suspension no aftermarket spindles or homemade strut towers front end should have some bounce.

9. **Bumpers** must appear stock and not exceed width of the front end but can be reinforced. Thickness of the bumper may not exceed 8 inches from front to back. **Example:** cutting ends off and sliding a pipe in will be allowed. May use plate or angle iron to secure the bumper from falling off. The piece used may only exceed the width of the front bumper pad by a few inches.
10. **Tires** NO Tractor or Digger tires on drive axle. Only Mud/ Snow tires can be used on the drive axle. Tubes and valve stem protectors are allowed.
11. **Cage** four post and roll bar are mandatory. No kickers allowed. Stock seat belts must be in good working order or a harness may be put in the car.
12. **Track Rules** no driver's door shots if the official feels the hit was intentional and the car will be black flagged from race.
13. When red lights come on all cars are to stop immediately. If the vehicle leaves the track area you may re-enter under idle not at full throttle.
14. Any two-digit number can be used in bright color so scorers can see it. No profanity or vulgar sayings on vehicles; this is a family show.

**1<sup>st</sup>. \$500, 2<sup>nd</sup> \$250, 3<sup>RD</sup> \$200 4<sup>TH</sup> \$175, 5<sup>TH</sup> \$100**

**Minimum of 5 cars for full payout**